

| PRODUCT DESCRIPTION | STANDARDS | VinylONE |
|----------------------------------------------|-------------------|-------------------------------------|
| Product | | VinylONE |
| Brand Origin | | South Korea |
| Type & Composition | | PVC Laminated Floor covering |
| Application | | Commercial, Residential |
| Surface treatment | | PU & Anti-bacterial, per design |
| Profile | | Beveled Edge |
| Tile Size (W X L mm) | ASTM F2421-05 | Plank: 184 x 950, Square :457 x 457 |
| Overall thickness (mm) | ASTM F386-02 | 3.0 |
| Wear layer thickness (mm) | EN 429 | 0.3 |
| Fire rating | EN 13501-1 | Bf1-S1 |
| | ASTM E 648 | Class 1 |
| | ASTM E 84 | 75 or less |
| | Mekel Burner Test | Pass |
| Heat Stability | ASTM F1514-03 | Pass |
| Dimensional Stability after exposure to heat | EN434 | Length: -0.08 Width: -0.09 |
| Abrasion resistance | ASTM D 3884 | 0.1% Loss |
| Resistance to Chemical | ASTM F925-02 | No change |
| Residual indentation | ASTM F 1914-07 | Average 0.007 |
| Slip resistance | ADA | Exceed ADA requirement |
| Static load limit | ASTM F970-07 | Average 0.007 |
| Coefficient of friction | ASTM C 1028-2007 | 0.7 |
| Residual indentation | EN 433 | ≥ 6 |
| Color fastness | ISO 105-B02 | ≥ 6 |
| Dimensional stability | EN 434 | Pass |
| Flexibility og Resilient flooring | ASTM F137-03 | No breaks, No cracks |
| Recyclable | | Yes |
| VOC emission test | ASTM D 5116-06 | Pass |

W: www.lafloorliving.com

Salesline: 6745-1407 / 8122-9122

Facebook: [lafloorliving](https://www.facebook.com/lafloorliving)